

### **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

### **Listing of Claims:**

1. (Currently Amended) A lighting device comprising:

a light guide plate;

a light guide disposed along a side end surface of the light guide plate;

and

a light emitting device disposed on an end surface of the light guide,

wherein a plurality of wedge-shaped grooves seen in cross section

extending in a thickness direction of the light guide is formed and arranged in a backside of the light guide on an opposite side of the light guide plate,

a metal reflective film ~~is formed on a side surface of the light guide,~~

in a distribution of a pitch between the grooves with respect to a distance from the end surface disposed with the light emitting device to groove, the pitch between the grooves is constant or linearly varied with respect to the distance from the end surface disposed with the light emitting device to the groove,

a depth of the groove is formed more deeply as the groove is positioned more distal from the end surface,

in a distribution of the depth of the groove with respect to the distance from the end surface disposed with the light emitting device to the groove, there ~~are~~ is a first area where the depth of the groove is constant or linearly increased with respect to the distance from the end surface to the groove, and a second area formed more distal from the light emitting device than the first area in which an increasing rate of the depth of the groove with respect to the distance from the end surface is greater than that in the first area, and

in two grooves adjacent to each other formed in at least one of the first and second area, a ratio of the depth of the groove formed on a side apart from the end surface to the depth of the other groove ranges from 1 to 1.005.

2. (Currently Amended) The lighting device according to claim 1, wherein in two grooves adjacent to each other formed in the first area, a ratio of the depth of the groove formed on a side apart from the end surface to the depth of the other groove ranges from more than 1 to less than 1.005.

3. (Original) The lighting device according to claim 1, wherein in two grooves adjacent to each other formed in the second area, a ratio of the depth of the groove formed on a side apart from the end surface to the depth of the other groove ranges from 1.005 to 1.015.

4. (Original) The lighting device according to claim 1, wherein in the first area, a distance  $x$  (mm) from the end surface disposed with the light emitting device and a depth  $y$  ( $\mu\text{m}$ ) of the groove at a position thereof satisfy expression  $y = a_1x + b_1$ , where  $a_1$  is larger than 0 and less than 0.5, and  $b_1$  ranges from 8.0 to 20.

5. (Currently Amended) The lighting device according to claim 1, wherein in the second area, the depth of ~~the a~~ groove is given by a quadratic function, cubic function or exponential function of the depth of the groove and the distance from the groove to the end surface disposed with the light emitting device.

6. (Currently Amended) The lighting device according to claim 5, wherein the distance from a position of an end of the second area on the light emitting device side to the end surface disposed with the light emitting device is less than 40 mm or less~~smaller~~ than two-thirds of an overall length of the intermediate light guide, and a depth  $y$  ( $\mu\text{m}$ ) of the groove and a distance  $x$  (mm) from the groove to the end surface disposed with the light emitting device satisfy expression  $y = a_2x^2 + b_2$ , where  $a_2$  ranges from 0.010 to 0.024, and  $b_2$  ranges from -20 to 13.

7. (Currently Amended) The lighting device according to claim 5, wherein the distance from a position of an end of the second area on the light emitting device side to the end surface disposed with the light emitting device is greater than 40 mm or greater~~smaller~~ than two-thirds of an overall length of the intermediate light guide, and

a depth  $y$  ( $\mu\text{m}$ ) of the groove and a distance  $x$  (mm) from the groove to the end surface disposed with the light emitting device satisfy expression  $y = a_3x^2 + b_3x + c_3$ , where  $a_3$  ranges from 0.050 to 0.080,  $b_3$  ranges from -5.7 to -3.7, and  $c_3$  ranges from 50 to 130.

8. (Original) The lighting device according to claim 5, wherein in the first area and the second area, a depth  $y$  ( $\mu\text{m}$ ) of the groove and a distance  $x$  (mm) from the groove to the end surface disposed with the light emitting device satisfy expression  $y = a_4x^3 + b_4x^2 + c_4x + d_4$ , where  $a_4$  ranges from 0.55 to 0.85,  $b_4$  ranges from -0.055 to -0.026,  $c_4$  ranges from 0.3 to 1.5, and  $d_4$  ranges from 8.0 to 20.

9. (Previously Presented) The lighting device according to claim 1, wherein in the distribution of the depth of the groove with respect to the distance from the end surface disposed with the light emitting device to the groove, there is a third area where the depth of the groove is constant irrespective of the distance from the end surface to the groove, and

the third area is formed at a position more distal from the light emitting device than the first area and the second area.

10. (Original) The lighting device according to claim 1, wherein a width of the light guide is 4 mm or greater, and

the pitch between the grooves is formed to be constant irrespective of the distance from the end surface disposed with the light emitting device or formed wider in accordance with the distance from the end surface.

11. (Previously Presented) The lighting device according to claim 10, wherein a pitch  $z$  ( $\mu\text{m}$ ) of the groove and a distance  $x$  (mm) from the end surface disposed with the light emitting device satisfy expression  $z = a_5x + b_5$ , where  $a_5$  is larger than 0 and less than 14, and  $b_5$  ranges from 180 to 250.

12. (Currently Amended) The lighting device according to claim 1, wherein a width of the light guide is below 4 mm, and

the pitch between the grooves is formed narrower in accordance with the a distance from the end surface disposed with the light emitting device.

13. (Original) The lighting device according to claim 12, wherein a pitch  $z$  ( $\mu\text{m}$ ) of the groove and a distance  $x$  (mm) from the end surface disposed with the light emitting device satisfy expression  $z = a_6x + b_6$ , where  $a_6$  ranges from -14 to 0, and  $b_6$  ranges from 280 to 350.

14. (Original) The lighting device according to claim 1, wherein the groove is formed into an isosceles triangle seen in cross section, and a vertex angle thereof is formed ranging from an angle of 95 to 120 degrees.

15. (Original) A liquid crystal display device comprising:  
the lighting device according to claim 1; and  
a liquid crystal panel.

16. (Currently Amended) A lighting device comprising:  
a light guide plate;  
a light guide disposed along a side end surface of the light guide plate;

and

a light emitting device disposed on an end surface of the light guide,  
wherein a plurality of wedge-shaped grooves seen in cross section  
extending in a thickness direction of the light guide is formed and arranged in a  
backside of the light guide on an opposite side of the light guide plate,  
a metal reflective film is formed on a side surface of the light guide,  
in a distribution of a pitch between the grooves with respect to a distance  
from the end surface disposed with the light emitting device to groove, the pitch  
between the grooves is linearly varied with respect to the distance from the end surface  
disposed with the light emitting device to the groove,

a depth of the groove is formed more deeply as the groove is positioned  
more distal from the end surface,

in a distribution of the depth of the groove with respect to the distance  
from the end surface disposed with the light emitting device to the groove, there are a

first area where the depth of the groove is linearly increased with respect to the distance from the end surface to the groove, and a second area formed more distal from the light emitting device than the first area in which an increasing rate of the depth of the groove with respect to the distance from the end surface is greater than that in the first area, and

in the first area, a distance  $x$  (mm) from the end surface disposed with the light emitting device and a depth  $y$  ( $\mu\text{m}$ ) of the groove at a position thereof satisfy expression  $y = a_1x + b_1$ , where  $a_1$  is larger than 0 and less than 0.5, and  $b_1$  ranges from 8.0 to 20.

17. (Currently Amended) A lighting device comprising:

a light guide plate;

a light guide disposed along a side end surface of the light guide plate;

and

a light emitting device disposed on an end surface of the light guide,

wherein a plurality of wedge-shaped grooves seen in cross section extending in a thickness direction of the light guide is formed and arranged in a backside of the light guide on an opposite side of the light guide plate,

a metal reflective film is formed on a side surface of the light guide,

in a distribution of a pitch between the grooves with respect to a distance from the end surface disposed with the light emitting device to groove, the pitch between the grooves is linearly varied with respect to the distance from the end surface disposed with the light emitting device to the groove,

a depth of the groove is formed more deeply as the groove is positioned more distal from the end surface,

in a distribution of the depth of the groove with respect to the distance from the end surface disposed with the light emitting device to the groove, there are a first area where the depth of the groove is linearly increased with respect to the distance from the end surface to the groove, and a second area formed more distal from the light emitting device than the first area in which an increasing rate of the depth of the groove with respect to the distance from the end surface is greater than that in the first area,

in the second area, the depth of the groove is given by a quadratic function, cubic function or exponential function of the groove and the distance from the groove to the end surface disposed with the light emitting device,

the distance from a position of an end of the second area on the light emitting device side to the end surface disposed with the light emitting device is smaller than two-thirds of an overall length of the intermediate light guide, and

a depth  $y$  ( $\mu\text{m}$ ) of the groove and a distance  $x$  (mm) from the groove to the end surface disposed with the light emitting device satisfy expression  $y = a_2x^2 + b_2$  or  $y = a_3x^2 + b_3x + c_3$  or  $y = a_4x^3 + b_4x^2 + c_4x + d_4$  where  $a_2$  ranges from 0.010 to 0.024,  $b_2$  ranges from -20 to 13,  $a_3$  ranges from 0.050 to 0.080,  $b_3$  ranges from -5.7 to -3.7,  $c_3$  ranges from 50 to 130,  $a_4$  ranges from 0.55 to 0.85,  $b_4$  ranges from -0.055 to -0.026,  $c_4$  ranges from 0.3 to 1.5, and  $d_4$  ranges from 8.0 to 20.

18. (Currently Amended) A lighting device comprising:

a light guide plate;

a light guide disposed along a side end surface of the light guide plate;

and

a light emitting device disposed on an end surface of the light guide,

wherein a plurality of wedge-shaped grooves seen in cross section extending in a thickness direction of the light guide is formed and arranged in a backside of the light guide on an opposite side of the light guide plate,

~~a metal reflective film is formed on a side surface of the light guide,~~

in a distribution of a pitch between the grooves with respect to a distance from the end surface disposed with the light emitting device to groove, the pitch between the grooves is linearly varied with respect to the distance from the end surface disposed with the light emitting device to the groove,

~~a depth of the groove is formed more deeply as the groove is positioned more distal from the end surface,~~

in a distribution of the depth of the groove with respect to the distance from the end surface disposed with the light emitting device to the groove, there ~~are~~is a first area where the depth of the groove is constant or linearly increased~~increasing~~ with

respect to the distance from the end surface to the groove, and a second area formed more distal from the light emitting device than the first area in which an increasing rate of the depth of the groove with respect to the distance from the end surface is greater than that in the first area,

in the second area, the depth of the groove is given by a quadratic function, cubic function or exponential function of the groove and the distance from the groove to the end surface disposed with the light emitting device,

in the distribution of the depth of the groove with respect to the distance from the end surface disposed with the light emitting device to the groove, there is a third area where the depth of the groove is constant irrespective of the distance from the end surface to the groove, and

the third area is formed at a position more distal from the light emitting device than the first area and the second area.

19. (Currently Amended) A lighting device comprising:

a light guide plate;

a light guide disposed along a side end surface of the light guide plate;

and

a light emitting device disposed on an end surface of the light guide,

wherein a plurality of wedge-shaped grooves seen in cross section extending in a thickness direction of the light guide is formed and arranged in a backside of the light guide on an opposite side of the light guide plate,

~~a metal reflective film is formed on a side surface of the light guide,~~

in a distribution of a pitch between the grooves with respect to a distance from the end surface disposed with the light emitting device to groove, ~~the pitch between the grooves is linearly varied with respect to the distance from the end surface disposed with the light emitting device to the groove,~~

a depth of the groove is formed more deeply as the groove is positioned more distal from the end surface,

in a distribution of the depth of the groove with respect to the distance from the end surface disposed with the light emitting device to the groove, there are a first area where the depth of the groove is linearly increased with respect to the distance

from the end surface to the groove, and a second area formed more distal from the light emitting device than the first area in which an increasing rate of the depth of the groove with respect to the distance from the end surface is greater than that in the first area,

in the second area, the depth of the groove is given by a quadratic function, cubic function or exponential function of the groove and the distance from the groove to the end surface disposed with the light emitting device,

a width of the light guide is 4 mm or greater, and

the pitch between the grooves is formed to be constant irrespective of the distance from the end surface disposed with the light emitting device or formed wider in accordance with the distance from the end surface, wherein a pitch  $z$  ( $\mu\text{m}$ ) of the groove and a distance  $x$  (mm) from the end surface disposed with the light emitting device satisfy expression  $z = a_5x + b_5$ , where  $a_5$  is larger than 0 and less than 14, and  $b_5$  ranges from 180 to 250.

20. (Canceled)

21. (Currently Amended) A lighting device comprising:

a light guide plate;

a light guide disposed along a side end surface of the light guide plate;

and

a light emitting device disposed on an end surface of the light guide,

wherein a plurality of wedge-shaped grooves seen in cross section extending in a thickness direction of the light guide is formed and arranged in a backside of the light guide on an opposite side of the light guide plate,

~~a metal reflective film is formed on a side surface of the light guide,~~

in a distribution of a pitch between the grooves with respect to a distance from the end surface disposed with the light emitting device to groove, ~~the pitch between the grooves is linearly varied with respect to the distance from the end surface disposed with the light emitting device to the groove,~~

a depth of the groove is formed more deeply as the groove is positioned more distal from the end surface,



in a distribution of the depth of the groove with respect to the distance from the end surface disposed with the light emitting device to the groove, there are a first area where the depth of the groove is linearly increased with respect to the distance from the end surface to the groove, and a second area formed more distal from the light emitting device than the first area in which an increasing rate of the depth of the groove with respect to the distance from the end surface is greater than that in the first area,

in the second area, the depth of the groove is given by a quadratic function, cubic function or exponential function of the groove and the distance from the groove to the end surface disposed with the light emitting device,

a width of the light guide is below 4 mm, and

the pitch between the grooves is formed narrower in accordance with the distance from the end surface disposed with the light emitting device, wherein a pitch  $z$  ( $\mu\text{m}$ ) of the groove and a distance  $x$  (mm) from the end surface disposed with the light emitting device satisfy expression  $z = a_6x + b_6$ , where  $a_6$  ranges from -14 to 0, and  $b_6$  ranges from 280 to 350.

22.-23 (Canceled)

24. (New) The lighting device according to claim 10, wherein the pitch between adjacent grooves is linearly widened as the distance between the adjacent grooves and the end surface disposed with the light emitting device is increased.

25. (New) The lighting device according to claim 1, wherein the reflective metal film is formed on a side surface of the light guide.

26. (New) The lighting device according to claim 1, further comprising a case covering the light guide and the light emitting device, wherein the reflective metal film is formed on a inner side of the case.